Datenblatt

UNI-T, UT131A, Digitales Multimeter, Palm size, mit 2mF Kapazitätsmessung

Order number:	UT131A
Hersteller:	UNI-T
EAN:	6935750513118
Herkunftsland:	China
Zolltarifnummer:	90303100
Gewicht:	0.319 kg

Die neue Generation der UT131-Serie definiert die Leistungsstandards für Digitalmultimeter der Einstiegsklasse neu. Das innovative Industriedesign sorgt dafür, dass diese Produkte einem Fall aus 2 Metern Höhe standhalten. Das neue LCD-Display-Layout bietet eine bessere Benutzererfahrung. Diese Serie stellt sicher, dass Anwender sicher in CAT II 250V Umgebung arbeiten können. Besondere Merkmale sind: 2mF-Kapazitätsprüfung (UT131A); Batterieprüfung (UT131B); Temperaturmessfunktion (UT131C); berührungslose Spannungsprüfung (NCV) (UT131D).

Eigenschaften:

- Übersichtliches LCD-Display
- Komfortable Schutzhülle, mit Messleitungsaufhängung
- 2 Meter Falltest, Präzisionsschutz
- Lauter Summerton
- Ergonomisches Design

Technische Spezifikationen

- Stromversorgung: 1,5V Batterie (R03) x 2
- Anzeige: 66mm x 51mm
- Produkt-Nettogewicht: 300g
- Produktfarbe Rot und Grau
- Produktgröße (B x H x T): 131mm x 95mm x 58mm
- Mitgeliefertes Zubehör: Messleitung, Bedienungsanleitung

Available downloads:

Download Datenblatt-UT131-Serie

All names and signs listed here are the property of the respective manufacturer. Misprints, changes & errors reserved.

Weitere Bilder:

SPECIFICATIONS

	Range	UT33A	UT33B	UT33C	UT33D
DC voltage (V)	200mV~1000V	±(0.5%+3)	±(0.5%+3)	±(0.5%+3)	±(0.5%+2)
AC voltage (V)	200mV~1000V	±(0.7%+3)			
	200V~280V		±(1.2%+3)	±(1.2%+3)	±(1.2%+10)
DC current (A)	200μA~10A	±(1.0%+3)	±(1%+2)		
	2000μA~10A			±(1.0%+2)	±(1.0%+2)
AC current (A)	200μA~10A	±(1.2%+3)			
Resistance (Ω)	200Ω~200MΩ	±(1.0%+3)			±(1.0%+2)
	200Ω~20MΩ		±(1.0%+2)	±(1.0%+2)	
Capacitance (F)	2nF~2mF	±(3%+3)			
Temperature	-40°C~1000°C			±(3%+4)	
	-40°F~1832°F			±(3.3%+4)	
Features					
Display count		2000	2000	2000	2000
Auto power off/Auto backlight off		√	√	√	√
Diode test/Continuity buzzer		√	√	√	√
Data Hold		2m	2m	2m	2m
Test probe holder		√	√	√	√
Range selection		Auto	Manual	Manual	Manual
Battery test			LOW BATT		
NCV					√

All names and signs listed here are the property of the respective manufacturer. Misprints, changes & errors reserved.